



## **CAT IV Insulation Tester/MultiMeter** with Wireless PC Interface

Combines a 1000V Insulation Tester

With a full-featured True RMS MultiMeter in a single, compact instrument

## **Features:**

- Wireless USB interface transmits measurement data to a PC
- Backlit super large triple display
- 125V, 250V, 500V, and 1000V test voltages
- Insulation Resistance from  $0.001 M\Omega$  to  $4000 M\Omega$
- Auto discharge of capacitive voltage
- Lock Power On Function for hands-free operation
- Data Hold and Auto Power Off
- Min/Max and Relative mode
- Waterproof (IP67) rugged double-molded design
- · Complete with remote receiver with USB cable, Windows® compatible software, heavy duty test leads, alligator clip test lead, Type K bead wire temperature probe with adapter, carrying case, and 6 x AA batteries



Measure the insulation resistance of transformer windings



Only a True RMS meter can give accurate readings of distorted waveforms





Continuous data streaming to your PC in real time

	EXTECH	יי אות ויי
		100 I*
	M O	
		-6
AUT0		
Îmi	10 • 20 •	30 • 40
Truo RMS	MultiMeter & Insu	lation Tector
<b>∢RECALL</b>	- +	PeakHOLD >
STORE	MAX MIN REL	HOLD
SETUP		AC+DC EXIT
LOCK	INSULATION	Yøusb
MODE		
	10A OFF V	V <sub>DC</sub>
4-20 mA%	COC	mV ACOC
μA		Hz%
	1	Ω +1:0
		Temp
		0.1
		IDC7
Auto Power	MG300	IP67
104		V Hz %Temp Ω-►+-⊕-) -
20A for 30	sec MAX CAT IV	600V
eve	ry 15 min A CAT III	1000V -
ДА ДА	-mA 10A 500mA ———————————————————————————————————	COM

Specifications	Range	Resolution	Accuracy
Insulation Tester	3		
Insulation Resistance	$4M\Omega$ , $40M\Omega$ , $400M\Omega$ , $4000M\Omega$	$0.001 \text{M}\Omega$	±3%
Insulation Test Voltages	125V, 250V, 500V, 1000V		
Multimeter			
AC Voltage	1000V	0.1mV	±1%
DC Voltage	1000V	0.01mV	±0.06%
AC Current	10A	0.1μΑ	±1.5%
DC Current	10A	0.01μΑ	±1.0%
Resistance	40ΜΩ	$0.01\Omega$	±0.3%
Capacitance	40mF	0.001nF	±3.5%
Frequency	100MHZ	0.001HZ	±0.1%
Duty Cycle	0.1 to 99.9%	0.01	±1.2%
Temperature	-58 to 1832°F	0.1°F	±1% + 4.5°F
	-50 to 1000°C	0.1°C	±1% + 2.5°C
4-20mA%	-25 to 125%	0.01%	
Continuity/Diode	Yes		
Power source	6 x AA batteries		
Dimensions	7.8 x 3.6 x 1.9" (200 x 92 x 50mm)		
Weight	20.5oz (582g)		

## **Ordering Information:**

MG300 ......CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (915MHz) MG300-NIST ......MG300 with Certificate of Calibration Traceable to NIST

MG302 ......CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (433MHz)

MG302-NIST ......MG302 with Certificate of Calibration Traceable to NIST

TL805.....Double Injected Test Leads

(NOTE: USA, Mexico, and Canada use 915MHz model and majority of other countries use 433MHz model)





