



KEM 340U Y/R

KEM Polycarbonate 10-630A

- IP66NW; Enclosure types U2
- IP66; Enclosure types U3, U4
- IP65; Enclosure types MF11, MF03, MF04
- Self-extinguishing material
- Wide operating temperature range
- Padlockable with 3 locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good UV resistance
- Good resistance against many chemicals
- Tested according to IEC 60947-3

KEM 16-40 A Installation guide video

>>

KEM 63-80 A Installation guide video

>>

Technical datasheet >>



Data subject to change without notice. Always confirm the data is correct from the seller.

Product details

SKU	KEM 340U Y/R
AC-21 400/415 V (A)	63 A
AC-21 690 V (A)	63 A
AC-22 400/415 V (A)	40 A
AC-22 690 V (A)	40 A
AC-23 400/415 V (A/kW)	40 A / 22 kW

Dimensional drawing

AC-23 690 V (A/kW) 32 A / 30 kW

Cable Area to Switch

Terminal (mm²) / Bolt size 1.5-16

Color Yellow / Red

EAN 6419410327777

Enclosure U2

Enclosure Type Polycarbonate

IP Rating 66

Number of Poles 3

Operation Front-operated

Switch type Load Break Switch

Weight (kg) 0.4

