CA722/2





Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the center of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, or 10 pole assemblies and are ready for immediate installation.

PRODUCT SPECIFICATION	
Rated Current	32 A
Torque	0.4 Nm

ORDERING INFORMATION			
CAT. NO.	DESCRIPTION	STD. PACK	
CA722/2	Pre Assembled Shorting Link assemblies with 2 poles	100	
CA722/3	Pre Assembled Shorting Links assemblies with 3 poles	100	
CA722/4	Pre Assembled Shorting Links assemblies with 4 poles	100	
CA722/5	Pre Assembled Shorting Links assemblies with 5 poles	100	
CA722/10	Pre Assembled Shorting Links assemblies with 10 poles	10	
CA722/100	Pre Assembled Shorting Links assemblies with 100 poles	10	

SUITABLE FOR		
CF4SP	4 sq.mm Single Level Fuse Terminal Blocks with Jumper possibility	
CF4SPD3	4 sq.mm screw clamp diode D3 (1N5820) Configuration Terminal Block	
CKT4SPH	CKT4SPH: 4 sq.mm Disconnect & Test Terminal Blocks with Hand operated Knife Type disconnecting contact and with Jumper possibility.	
CTL2.5UH	2.5 sq.mm Three Level Terminal Blocks suitable for sensor & actuator application	
CTL2.5UH(I.S)D2	2.5 sq.mm Three Level Terminal Blocks with Diode suitable for sensor & actuator application	
CTS4UNV0	4 sq.mm Feed Through Terminal Blocks	
CKT4SPSC	4 sq.mm Knife Type Disconnect & Test Terminal Blocks with Socket screws spring loaded.	
CDLG4(I.S)	4 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points.	
CF4SPFT	4 sq.mm Standard Feed Through Terminal Blocks	
CTL2.5U(I.S)	2.5 sq.mm Three Level internally shorted Terminal Blocks	
CTL2.5UL	2.5 sq.mm Three Level Feed through Terminal Block with LED	
CTS2.5UE	2.5 sq.mm, 6 mm thick Feed Through Terminal Block	
CTS4UNCR	4 sq.mm Feed Through Terminal Blocks	
CCC4U	Component carrier terminal block	
CDL4UN	4 sq.mm Double Level Terminal Blocks.	
CDL4UN(I.S)	4 sq.mm Double Level Internally Shorted Terminal Blocks.	
CDLG4	4 sq.mm Double Level Earthing Terminal Blocks.	
CF4SPD1	4 sq.mm screw clamp diode D (1N4007) Configuration Terminal Block	
CF4SPL	4 sq.mm Single Level Fuse Terminal Blocks with LED indication.	





SUITABLE FOR		
CTL2.5U	2.5 sq.mm Three Level Feed through Terminal Blocks	
CTL2.5UHL	2.5 sq.mm Three Level Terminal Blocks with LED suitable for sensor & actuator application	
CTS4UN	4 sq.mm Standard Feed Through Terminal Blocks	
CMC1-2	4 sq.mm Multiple Connection Terminal Blocks with 3 connection points.	
CMC2-2	4 sq.mm Multiple Connection Terminal Blocks with 4 connection points.	
CF4SPD2	4 sq.mm screw clamp diode D2 (1N5408) Configuration Terminal Block	
CKT4SP	4 sq.mm Knife Type Disconnect & Test Terminal Blocks with Socket screws and with possibility of using Jumpers	
CTS4UNP	4 sq.mm Feed Through Philips Head screw Terminal Blocks	
CM4USC	4 sq.mm Spring Loaded Feed Through Terminal Blocks	