







GROUND / EARTH TERMINAL BLOCKS

These Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with the DIN rails. They are green / yellow colourcoded as per industry standards.

The terminals with  & IECEx approval can be used in potentially explosive atmosphere. For detailed information refer page 175.

CSCG2.5T



Width (Thickness) x Length	5 x 58 mm		
Height with DIN 35 x 7.5 / 35 x 15 mm Rail	37.5 mm / 45.5 mm		
Connection Possibility as per	IEC	UL - CSA	
With 1 Conductor per clamp	Stranded / Flexible	0.2 - 2.5 mm ²	22 - 12 AWG
	Solid	0.2 - 4.0 mm ²	22 - 10 AWG
	with Ferrule / Lug	0.2 - 2.5 mm ²	22 - 12 AWG
With 2 same size Conductors per clamp	with TWIN Ferrule / Lug	0.2 - 1.5 mm ²	22 - 14 AWG
Wire Stripping Length	11 mm		
Approvals			
Insulation Material / Comparative Tracking Index	Polyamide 66 / 1		
Rated Impulse Voltage / Pollution Degree	8 KV / 3		
	Type / Cat. No.	Standard Pack	
Terminal Block	CSCG2.5T	100	
End Plate 	EPCSC2.5T	50	
Mounting Rail (Refer Pg. 154 for details) 	CA701 CA701-15	50 m 50 m	
Marking Tags (Refer Pg. 157 for details) 	CA509/K5	100	
Screw Driver for actuating the Spring Clamp 	SCS0.5/3 Blade size: 0.5 x 3 mm	10	

CSCG4T



6 x 65 mm

45.0 mm / 52.2 mm

IEC	UL - CSA
0.2 - 4.0 mm ²	22 - 10 AWG
0.2 - 6.0 mm ²	
0.2 - 4.0 mm ²	22 - 10 AWG

0.2 - 2.5 mm² 22 - 14 AWG

15 mm




Polyamide 66 / 1

8 KV / 3

Type / Cat. No.	Standard Pack
CSCG4T	100
EPCSC4T	50
CA701	50 m
CA701-15	50 m
CA509/K6	100
SCS0.6/3.5 Blade size: 0.6 x 3.5 mm	10

CSCG6T



8 x 72 mm

47.8 mm / 55.2 mm

IEC	UL - CSA
0.2 - 6.0 mm ²	22 - 8 AWG
0.2 - 10.0 mm ²	
0.2 - 6.0 mm ²	22 - 8 AWG

0.2 - 4.0 mm² 22 - 10 AWG

15 mm



Polyamide 66 / 1

8 KV / 3

Type / Cat. No.	Standard Pack
CSCG6T	100
EPCSC6T	50
CA701	50 m
CA701-15	50 m
CA509/K8	100
SCS0.8/4 Blade size: 0.8 x 4 mm	10

CSCG10T



10 x 75 mm

51.6 mm / 59.0 mm

IEC	UL - CSA
1.5 - 10.0 mm ²	16 - 6 AWG
1.5 - 10.0 mm ²	
1.5 - 10.0 mm ²	16 - 6 AWG

1.5 - 6.0 mm² 16 - 8 AWG

18 mm



Polyamide 66 / 1

8 KV / 3

Type / Cat. No.	Standard Pack
CSCG10T	100
EPCSC10T	50
CA701	50 m
CA701-15	50 m
CA509/K10	100
SCS0.8/4 Blade size: 0.8 x 4 mm	10

